

TECHNICAL SUBMITTAL FOR EXTREME 300 LOADING CYLINDER

GENERAL	
Storage Capacity	300 Litres
Height	1830mm
Diameter	710mm
Weight (Empty)	77 kg
Weight (Full)	377 kg
Electrical Supply	230 V 1 ph 50 Hz
HWS PERFORMANCE (BASED ON A MAXIMUM INPUT OF 120 KW AT 80°C)	
1st Hour Output at 60°C	2370 Litres
10 Minute Peak at 60°C	645 Litres
Continuous Flow at 60°C	2070 Litres
TECHNICAL DATA	
Cylinder Material	Stainless Steel
Plate Heat Exchanger Material	Stainless Steel
Plate Heat Exchanger Capacity	Up to 120 kW at 80°C
Primary Flow Connection	28mm
Primary Return Connection	28mm
MCWS Connection	1¼" BSP
DHWS Connection	1¼" BSP
Secondary Return Connection	1" BSP
Maximum Primary Temperature	90°C
P & T Valve (Integral)	10 bar / 90°C
Maximum Working Pressure (Unvented)	6 bar
Maximum Working Pressure (Open Vented)	10 bar
ENVIRONMENTAL DATA	
Standing Thermal Loss	163 MJ per Month
Energy Efficiency Class	B

